## **DATASHEET**




Code: 72CSHSW

## Hartland CFX | HARTLAND CFX RANGE | Power Sockets


### Product Image



### Wiring



#### **Dimensions**



Insert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)
Insert Colour	White
EAN13 Barcode	5017504250034
Commodity Code	85363010
Luckins TSI	388237401
Dimensions(Nominal)	Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips
Switched Poles	None
Current Rating	20VA
Voltage	220/250V AC
Maximum Load	200/250V input; 115/230V 20VA output
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	None
Terminal Capacity 1	5 x1mm²
Terminal Capacity 2	4x1.5mm²
Terminal Capacity 3	3x2.5mm²
Terminal Capacity 4	2x4mm² Multi-strand
Terminal Capacity 5	1x6mm²
Earth Terminal Capacity 1	9x1mm²
Earth Terminal Capacity 2	6x1.5mm²
Earth Terminal Capacity 3	4x2.5mm²
Earth Terminal Capacity 4	2x4mm² Multi-strand
Earth Terminal Capacity 5	1x6mm²
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

Standard/Approval

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was expected to 5/11/2023 9/417-28 AMESOF.

BS EN 61558-2-5 + BS 4573

# **DATASHEET**



Code: 72CSHSW

# Hartland CFX | HARTLAND CFX RANGE | Power Sockets

**Additional Notes** 

Must be mounted vertically. Shuttered: Yes. Box

Depth 47mm

T: +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com