# **DATASHEET**




Code: 78SPNBK-B

# Hartland | HARTLAND RANGE | Connection Units


#### Product Image



### Wiring



### **Dimensions**



Insert Type 1 gang 13A Double Pole Fused Spur + Neon  Insert Colour Black Nickel/Black  EAN13 Barcode 5017503286928  Commodity Code 85369010  Luckins TSI 386903423  Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Weight 120 GR  Switched Poles Double  Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Full Terminal Capacity 1 6x1mm²  Full Terminal Capacity 1 6x1mm²
EAN13 Barcode 5017503286928  Commodity Code 85369010  Luckins TSI 386903423  Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Weight 120 GR  Switched Poles Double  Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Commodity Code Luckins TSI 386903423  Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Weight 120 GR Switched Poles Double Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 1P Rating IP 2XD  Contact Gap Minimum Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Luckins TSI 386903423  Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Weight 120 GR  Switched Poles Double  Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Dimensions(Nominal)Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mmWeight120 GRSwitched PolesDoubleCurrent Rating13 AmpVoltage220/250V ACMaximum Load13 AmpMains Frequency50HzIP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 13x2.5mm²Terminal Capacity 22x4mm² Multi-StrandTerminal Capacity 31x6mm²Earth Terminal Capacity 16x1mm²
Switched Poles Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 2x4mm² Multi-Strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm²
Current Rating 13 Amp  Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Voltage 220/250V AC  Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Maximum Load 13 Amp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 2x4mm² Multi-Strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm²
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Terminal Capacity 2 2x4mm² Multi-Strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²
Earth Terminal Capacity 1 6x1mm <sup>2</sup>
Forth Tourist Council 10 11 5 4 5 m s <sup>2</sup>
Earth Terminal Capacity 2 5x1.5mm <sup>2</sup>
Earth Terminal Capacity 3 3x2.5mm²
Earth Terminal Capacity 4 2x4mm² Multi-Strand
Earth Terminal Capacity 5 1x6mm²
Product Class 1 Must be earthed
Ambient Operating -5° to +40°C Temperature
Recommended Location Internal Use Only
Maximum Installation Altitude 2000m

BS 1363-4

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

Standard/Approval

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.