DATASHEET



Code: 79TCMB

Hartland | HARTLAND RANGE | Telephone and Data Outlets

Product Image




Wiring

Pin No.	BT Wiring Schedule Colour Codes: Striped Wires
\Box	GREEN / White
2	BLUE / White
3	ORANGE / White
4	WHITE / Orange
5	WHITE / Blue
6	WHITE / Green
Ma	ain Wire Colour shown in CAPITALS

Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.

The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.

Dimensions



Insert Type	1 gang Telephone Master
Insert Colour	Black
EAN13 Barcode	5017503291649
Commodity Code	85176990
Luckins TSI	386903960
Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm
Weight	100 GR
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 1 Earth Terminal Capacity 2	5x1mm ² 4 x 1.5mm ²
	<u> </u>
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 2 Earth Terminal Capacity 3	4 x 1.5mm2 3 x 2.5mm2
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed (ref BS7671 415.2.1)
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed (ref BS 7671 415.2.1) -5° to +40°C Internal Use Only

BS 6312:2:2

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

Standard/Approval

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was expected on 2/24/2023 3/0912 PM ES CE