DATASHEET



Code: 7CBC2XLEDITB100

Hartland CFX | HARTLAND CFX RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Product Image 2 gang 100W LED Trailing/Leading Edge Push On/Off

Weight

Insert Colour Copper Bronze

EAN13 Barcode 5017504079772

Commodity Code 85365015

Luckins TSI 403364453

Dimensions(Nominal)Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm

Rotary 2 Way Switching Dimmer

3.011

Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips

268 GR

Switched Poles Single

Current Rating 0.3A Per Gang

Voltage 230V AC

Maximum Load 5-70W Per Gang

Mains Frequency 50Hz

IP Rating IP2XD

Terminal Capacity 1 2X1mm²

Terminal Capacity 2 2X1.5mm²

Earth Terminal Capacity 1 5x1mm²

Earth Terminal Capacity 2 4X1.5mm²

Earth Terminal Capacity 3 3X2.5mm²

Earth Terminal Capacity 4 1X4mm² Multi-Strand

Earth Terminal Capacity 5 1X6mm²

Product Class 1 Face plate muct be earthed

Ambient Operating -5°C to +40°C Temperature

Recommended Location Internal Use Only

Maximum Installation Altitude 2000m

Standard/Approval BS EN 60669-2-1


Additional Notes Trailing Edge & Leading Edge Dimmer





Dimensions

Wiring



R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated on 5/11/2023 10:00:19 AM E&OE