# DATASHEET

making connections beautifully

Hamilton


# Code: 7CBCR222BL-B

# Hartland CFX | HARTLAND CFX RANGE | Rocker Switches


## Product Image



### Wiring



#### Dimensions



Insert Type2 gang 20AX 2 Way RockerInsert ColourBlack/BlackEAN13 Barcode5017504011024Commodity Code85363030Luckins TSI398271538
EAN13 Barcode     5017504011024       Commodity Code     85363030
LUCKIIIS I J 3902/1330
<b>Dimensions(Nominal)</b> Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm
Weight 159 GR
Fixing Hole CentresBox Fixing = 60.3mm Grid Fixing = CFX Clips
Switched Poles Single
Current Rating 20AX
<b>Voltage</b> 220/250V AC
Maximum Load 20 Amp inductive
Mains Frequency50Hz
IP Rating IP2XD
Contact Gap Minimum 3mm
Terminal Capacity 1 $5x1mm^2$
Terminal Capacity 2 $4x1.5mm^2$
Terminal Capacity 3 $2x2.5mm^2$
Terminal Capacity 4 2x4mm <sup>2</sup> Multi-strand
Terminal Capacity 51x6mm²
Earth Terminal Capacity 1 6x1mm <sup>2</sup>
Earth Terminal Capacity 2 5x1.5mm <sup>2</sup>
Earth Terminal Capacity 3 3x2.5mm <sup>2</sup>
Earth Terminal Capacity 4 2x4mm <sup>2</sup> Multi-strand
Earth Terminal Capacity 5 1x6mm <sup>2</sup>
Product Class 1 Must be earthed
Ambient Operating-5° to +40°CTemperature
Recommended Location Internal Use Only
Maximum Installation Altitude 2000m
Standard/Approval BS EN 60669-1

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

 $\textbf{E:} info@hamilton-litestat.com | \textbf{W:} www.hamilton-litestat.com | \textbf{W$ 

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated on 5/11/2023 10:01:56 AM E&OE