
DATASHEET

Code: 8G22SS2SB-W Sheer G2 | SHEER G2 RANGE | Power Sockets



Wiring



Dimensions

| Insert Type | 2 gang 13A Double Pole Switched Socket |
|----------------------------------|---|
| Insert Colour | Satin Brass/White |
| EAN13 Barcode | 5017504095079 |
| Commodity Code | 85363010 |
| Dimensions(Nominal) | Double: Height = 85mm Width = 144mm Depth = 1.5mm + 2.7mm Gasket |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips |
| Switched Poles | Double |
| Current Rating | 13 Amp |
| Voltage | 220/250V AC |
| Maximum Load | 13 Amp |
| Mains Frequency | 50Hz |
| IP Rating | IP2XD |
| Contact Gap Minimum | 3mm |
| Terminal Capacity 1 | 4x2.5mm ² |
| Terminal Capacity 2 | 3x4mm² |
| Terminal Capacity 3 | 2x6mm² Multi-Strand |
| Terminal Capacity 4 | 1x10mm² |
| Earth Terminal Capacity 1 | 4x2.5mm² |
| Earth Terminal Capacity 2 | 3x4mm² |
| Earth Terminal Capacity 3 | 2x6mm² Multi-Strand |
| Earth Terminal Capacity 4 | 1x10mm² |
| Product Class 1 | Must be earthed |
| Ambient Operating Temperature | -5° to +40°C |
| Recommended Location | Internal Use Only |
| Maximum Installation Altitude | 2000m |
| Standard/Approval | BS 1363-2 |
| Additional Notes | Dual Earth: Yes |

Hamilton

making connections beautifully

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated on 4/27/2023 11:56:14 AM E&OE