Value+ Ceiling and Wall Light 10W 3000K 700lm Non-Dimmable

Partcode: ILBHE028 / Page: 1



Low-energy LED IP44 Value+ ceiling and wall light, suitable for all indoor areas such as hallways, stairways, walls and ceilings including bathrooms (Zone 2) and covered (sheltered) external areas, such as porches. PMMA Diffuser provides a soft light. Long life expectancy of 25,000 hours based on normal usage. 2 year warranty.

Product Details

Partcode: ILBHE028 Check Code: 991543 Range Name: Value+ Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: Bulkheads-Ceiling-Wall Lights Warranty: 2 Years CE / RoHS: Yes

Physical Data

Product Finish: Matt white Optic: PMMA diffuser Material: PMMA, Metal Construction: Metal base and PMMA diffuser

www.integral-led.com

integral LED

Partcode: ILBHE028 / Page: 2

Physical Data

Depth: 85mm Diameter: 250mm Weight (Unpackaged Single Unit): 360g

Electrical Data

Voltage Range: 220-240V Power Consumption: 10.0 Watts Electric Current: AC Ampage: 82.00mA Frequency Range: 50/60 Hz Power Factor: >=0.50 Dimming: Non-dimmable LVD Certified: Yes EN: EN-60598

Light Data


Lumens: 700lm Lumens per Watt: 70.0lm/W Beam Angle: 100° Correlated Colour Temperature (CCT): 3,000k Colour Temperature: Warm White Colour Rendering Index (CRI): >=80 LED Type: Surface mounted device (SMD) Instant on - Less than 1 second: Yes Lifetime: 25,000 hrs Switching Cycles: >12,500 X

www.integral-led.com



Partcode: ILBHE028 / Page: 3

Environmental



Lowest Operating Temperature: 0 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP44 Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788223696 Packaged Weight (Unit of 1): 596g Length (unit of 1): 275mm Width (unit of 1): 275mm Depth (unit of 1): 105mm **Outer packaging info available on website**

Product data last updated on: Monday, August 7, 2017 - 14:34

www.integral-led.com