

**TOUGSHELL BATTEN TWIN MICROWAVE SENSOR IP65 63w 7500lm 4000K
120 BEAM ANGLE 12LM/W 5FT NON-DIMM NON-LINKABLE**

ILBTD047



The Tough-Shell Batten features a tough IK08 and IP65 dust and waterproof polycarbonate casing with secure clips. The frosted diffuser provides even light distribution. Ideal for demanding environments such as warehouses, factories, car parks and more. This model features an integrated Microwave Sensor to provide light only when needed, further increasing efficiency.

Details

Quick Order Code:	487407
Barcode:	5055788239949
Category:	Luminaires
Range Name:	Tough-Shell
Type:	Twin
Product Type:	Battens
Product Body Finish:	Matt white
Market Segment:	Indoor commercial, Industrial, residential
Finish:	Matt White
Features:	Microwave Sensor
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	1550
Product Depth (mm):	83
Product Width (mm):	123
Product Weight (g):	2600
Optic:	Polycarbonate diffuser with Stainless Steel Clips
Material:	Polycarbonate
Construction:	Injection moulding
Bulb or Luminaire Shape:	Linear
Luminaire Fixing:	Wall/Ceiling mounted
Mounting Type:	Rear & Side Cable Entry
Placement / Application:	Indoor, General Lighting

Electrical Data



	63
Power Consumption (w):	0.9
Power Factor:	220-240
Input Voltage (V):	Non-Dimmable
Dimming:	Yes
Driver Included:	AC
Electric Current:	EN-60598
EN:	Yes
LVD Certified:	

Light Data

Luminous Flux in Lumens (lm):	7500
Luminous efficacy (lm/W):	119
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature Name:	Cool White
Beam Angle:	120
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	30000
Switching Cycles:	50000
Useful Lumens (lm):	7500

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
New Energy Rating:	E
EU Luminaire:	L
Hg 0% (Mercury Free):	Yes
IK Rating (Impact Protection):	IK08
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Packaging

Package Weight (g):	2840
Package Length (mm):	1551
Package Width (mm):	123
Package Depth (mm):	83

Portal.integral-led.com