LIGHTSPAN SLIM BATTEN MOTION SENSOR 4800LM 40W 4000K 120 BEAM 120LM/W 1200MM 4FT NON-DIMM INTEGRAL

ILBTF076



This highly efficient and attractive LED batten features a compact, low-profile body with a stylish brushed aluminium finish that will look great in offices, schools and other commercial or public sector environments. These battens run at a highly efficient 120lm/W so you can drastically reduce your energy costs over legacy technology luminaires.

Details

Quick Order Code: 627586 Barcode: 5055788243106 Luminaires Category: Lightspan Slim Range Name: Twin Type: **Product Type:** Battens **Product Body Finish:** Brushed aluminium **Market Segment:** Indoor Finish: Brushed aluminium Microwave Sensor Features: Warranty (Years): 3 CE RoHS: Yes

Physical Data

Product Length (mm): Product Depth (mm): Product Width (mm): Product Weight (g): Optic: Material: Construction: Bulb or Luminaire Shape: Luminaire Fixing: Mounting Type: Placement / Application: 1200 38 72 720 Polycarbonate Aluminium Injection moulding Linear Ceiling Rear & Side Cable Entry Lightspan Slim


Electrical Data

	40
Power Consumption (w):	0.9
Power Factor:	220-240
Input Voltage (V):	Non-Dimmable
Dimming:	AC
Electric Current:	Yes
LVD Certified:	
Light Data	

Luminous Flux in Lumens (Im):	4800
Luminous efficacy (Im/W):	120
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature Name:	Cool White
Beam Angle:	120
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Lifetime (hours):	35000
Switching Cycles:	100000
Useful Lumens (Im):	4800

Environment

LVD Certified:	Yes
CE RoHS:	Yes
EU Luminaire:	L
IK Rating (Impact Protection):	IK08
IP Rating (Ingress Protection):	IP20



Packaging

Package Weight (g):	935
Package Length (mm):	1205
Package Width (mm):	77
Package Depth (mm):	42

Portal.integral-led.com