

Recess Pro Downlight IP44 150mm cutout 29W 3000lm 105lm/W 4000K Dimmable Finish-Matt white

Partcode: ILDL150H018 / Page: 1



Recess Pro is a range of high-performance aluminium LED downlights with outstanding efficiency and extra-long lifetime. Ideal for replacement of traditional recessed CFL downlights. The deep-recessed design ensures a low-glare. The Recess Pro family is engineered to reduce your lighting energy consumption by up to 50%.

This range of well-finished, lightweight and IP44 protection rated downlights are suitable for placement in Zones 1 and 2 of bathrooms/washrooms as well as common indoor spaces. The included easy to use loop-in/loop-out driver with push-fit connector provides for a quick and safe installation.

[Watch Video](#)

Product Details

Partcode: ILDL150H018

Check Code: 250627

Range Name: Recess Pro

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor

Product Type: LED Downlights

Warranty: 3 Years

CE / RoHS: Yes

Physical Data

Product Finish: Matt white

Optic: PMMA diffuser

Material: Aluminium

Partcode: ILDL150H018 / Page: 2

Physical Data

Depth: 92mm

Diameter: 180mm

Weight (Unpackaged Single Unit): 770g

Cut Out Diameter: 150mm

Luminaire Fixing: Wall/Ceiling mounted

Electrical Data

Power Consumption: 29.0 Watts

Driver included: Yes

Dimming: Dimmable

LVD Certified: Yes

EN: EN 60598, EN 55015, EN 61547, EN 61000

Light Data

Lumens per Watt: 105.0lm/W

Beam Angle: 75°

Correlated Colour Temperature (CCT): 4000k

Colour Temperature: Cool White

Colour Rendering Index (CRI): ≥ 80


LED Type: Surface mounted device (SMD)

Lifetime: 60,000 hrs

Switching Cycles: $>15,000$ X

Partcode: ILDL150H018 / Page: 3

Environmental



Lowest Operating Temperature: -10 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP44

Hg 0% (Mercury Free): Yes

Packaging

EAN Barcode (unit of 1): 5055788250319

Packaged Weight (Unit of 1): 1,070g

Length (unit of 1): 215mm

Width (unit of 1): 215mm

Depth (unit of 1): 120mm

Outer packaging info available on website

Product data last updated on: Thursday, February 27, 2020 - 11:58