


Multi-Fit Downlight 12W 4000K 1020lm, 65-160mm cut out, Non-dimmable

Partcode: ILDL160-65G006 / Page: 1



This ultra-thin (15.5mm) downlight is supplied with configurable brackets and clips allowing for installation in a cut-out from 65-160mm as well as having a surface mount installation option. Visible flicker is eliminated with the integrated driver and a frosted diffuser provides uniform light.

Product Details

Partcode: ILDL160-65G006

Check Code: 078090

Range Name: Multi-Fit

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: CFL-PL and 2D replacements

Warranty: 3 Years

CE / RoHS: Yes

Physical Data

Product Finish: Matt white

Optic: Opal diffuser

Material: Aluminium, PS

Construction: Die cast Aluminium body, PS sheet diffuser

Physical Data

Depth: 16mm
Diameter: 180mm
Weight (Unpackaged Single Unit): 230g
Cut Out Diameter: 65-160mm
Luminaire Fixing: Recess or surface mounted

Electrical Data

Voltage Range: 220-240V
Power Consumption: 12.0 Watts
Driver included: Integrated
Electric Current: AC
Frequency Range: 50/60 Hz
Power Factor: ≥ 0.50
Wattage Equivalent: 15 Watts
Dimming: Non-dimmable
LVD Certified: Yes
EN: EN-60598

Light Data

Lumens: 1,020lm
Lumens per Watt: 85.0lm/W
Beam Angle: 120°
Correlated Colour Temperature (CCT): 4,000k
Colour Temperature: Cool White
Colour Rendering Index (CRI): ≥ 80
LED Type: Surface mounted device (SMD)
Lifetime: 30,000 hrs
Switching Cycles: $> 15,000$ X

Environmental

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP20

Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788241188

Packaged Weight (Unit of 1): 300g

Length (unit of 1): 225mm

Width (unit of 1): 189mm

Depth (unit of 1): 30mm

Outer packaging info available on website

Product data last updated on: Thursday, November 1, 2018 - 16:00