Recess Pro Downlight IP44 200mm cutout 35W 3850lm 110lm/W 3000K Dimmable Finish-Matt white



Recess Pro is a range of high-performance aluminium LED downlights with outstanding efficiency and extra-long lifetime. Ideal for replacement of traditional recessed CFL downlights. The deep-recessed design ensures a low-glare. The Recess Pro family is engineered to reduce your lighting energy consumption by up to 50%.

This range of well-finished, lightweight and IP44 protection rated downlights are suitable for placement in Zones 1 and 2 of bathrooms/washrooms as well as common indoor spaces. The included easy to use loop-in/loop-out driver with push-fit connector provides for a quick and safe installation.

Watch Video

Product Details

Partcode: ILDL200H019 Check Code: 896775 Range Name: Recess Pro Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor Product Type: LED Downlights Warranty: 3 Years CE / RoHS: Yes

Physical Data

Product Finish: Matt white Optic: PMMA diffuser Material: Aluminium

integral LED

Product Specification Sheet

Partcode: ILDL200H019 / Page: 2

Physical Data

Depth: 123mm Diameter: 230mm Weight (Unpackaged Single Unit): 1330g Cut Out Diameter: 200mm Luminaire Fixing: Wall/Ceiling mounted

Electrical Data

Power Consumption: 35.0 Watts Driver included: Yes Dimming: Dimmable LVD Certified: Yes EN: EN 60598, EN 55015, EN 61547, EN 61000

Light Data


Lumens per Watt: 110.0lm/W Beam Angle: 75° Correlated Colour Temperature (CCT): 3000k Colour Temperature: Warm White Colour Rendering Index (CRI): >=80 LED Type: Surface mounted device (SMD) Lifetime: 60,000 hrs Switching Cycles: >15,000 X

www.integral-led.com



Partcode: ILDL200H019 / Page: 3

Environmental



Lowest Operating Temperature: -10 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP44 Hg 0% (Mercury Free): Yes

Packaging

EAN Barcode (unit of 1): 5055788250975 Packaged Weight (Unit of 1): 1,790g Length (unit of 1): 265mm Width (unit of 1): 265mm Depth (unit of 1): 150mm

Outer packaging info available on website

Product data last updated on: Thursday, February 27, 2020 - 11:58

www.integral-led.com