Lux Hi-Brite 45 Downlight 45mm cutout 9W 500lm 58lm/W 3000K Non-Dimmable Finish-A Matt Black



Lux Hi-Brite range is uniquely designed to provide maximum lumen output from a very compact body. Minimum glare is achieved from a deep-recessed construction, guaranteeing comfortable light.

Lux Hi-Brite downlights are ideal for applications requiring high performance in limited spaces, such as hospitality, retail or commerce. The stylish fixed and tiltable finishes can illuminate a wide range of areas. Complement with Lux Mini range for coherent multilevel lighting design.

Product Details

Partcode: ILDL45K002 Check Code: 782523 Range Name: Lux Hi-Brite 45 Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: LED Downlights Warranty: 3 Years CE / RoHS: Yes

Physical Data

Product Finish: Matt Black Optic: PMMA lens Material: Aluminium

www.integral-led.com

integral LED

Partcode: ILDL45K002 / Page: 2

Physical Data

Depth: 56mm Diameter: 60mm Weight (Unpackaged Single Unit): 190g Cut Out Diameter: 45mm Luminaire Fixing: Wall/Ceiling mounted

Electrical Data

Power Consumption: 9.0 Watts Driver included: Yes Dimming: Non-dimmable LVD Certified: Yes EN: EN 60598, EN 55015, EN 61547, EN 61000

Light Data


Lumens: 500lm Lumens per Watt: 58.0lm/W Beam Angle: 30° Correlated Colour Temperature (CCT): 3000k Colour Temperature: Warm White Colour Rendering Index (CRI): >=80 LED Type: Chip-on-board (COB) Lifetime: 60,000 hrs Switching Cycles: >15,000 X

www.integral-led.com



Partcode: ILDL45K002 / Page: 3

Environmental



Lowest Operating Temperature: -10 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

Packaging

EAN Barcode (unit of 1): 5055788250494 Packaged Weight (Unit of 1): 260g Length (unit of 1): 110mm Width (unit of 1): 110mm Depth (unit of 1): 75mm

Outer packaging info available on website

Product data last updated on: Thursday, February 27, 2020 - 11:14

www.integral-led.com