# Low-Profile 70mm-75mm cut-out IP65 Fire Rated Downlight 6W (40W) 4000K 440Im 38 deg beam angle Non-Dimmable



These low-profile lamps are fire rated to 30, 60 and 90 minutes, Air Tightness compliant with Part C and Part L and Resistance to Sound compliant with Part E. Warm White and Cool White colour temperature options and dimmable or non-dimmable options are available. Importantly, these lamps are IP65 rated and designed to offer the safety and quality of other Fire Rated Downlights but with a lower price-tag.

## **Product Details**

Partcode: ILDLFR70B004 Check Code: 233935 Range Name: Low-profile Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: Fire Rated Warranty: 3 Years CE / RoHS: Yes

## **Physical Data**

Product Finish: Matt white Spot Type: COB Optic: Clear Refractor Material: Aluminium alloy, Iron, Intumescent material, Steel Construction: Extruded Aluminium heat-sink, Iron body, Steel springs and mounting plate

## www.integral-led.com

## integral LED

Partcode: ILDLFR70B004 / Page: 2

#### **Physical Data**

Length: 58mm Diameter: 85mm Weight (Unpackaged Single Unit): 280g Luminaire Fixing: Recess mounted Fire Rating: 30, 60, 90

#### **Electrical Data**

Voltage Range: 220-240V Power Consumption: 6.0 Watts Driver included: Yes Electric Current: AC Ampage: 300.00mA Frequency Range: 50/60 Hz Power Factor: >=0.90 Wattage Equivalent: 40 Watts Dimming: Non-dimmable LVD Certified: Yes EN: EN-60598

## **Light Data**


Lumens: 440lm Lumens per Watt: 73.0lm/W Beam Angle: 38° Correlated Colour Temperature (CCT): 4,000k Colour Temperature: Cool White Colour Rendering Index (CRI): >=80 LED Type: Chip on board (COB) Instant on - Less than 1 second: Yes Lifetime: 25,000 hrs Switching Cycles: >12,500 X

## www.integral-led.com



Partcode: ILDLFR70B004 / Page: 3

#### **Environmental**



Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 45 degrees IP (Ingress Protection) Rating: IP65 Hg 0% (Mercury Free): Yes

## Packaging

EAN Barcode (unit of 1): 5055788223412 Packaged Weight (Unit of 1): 350g Length (unit of 1): 105mm Width (unit of 1): 100mm Depth (unit of 1): 80mm

## Outer packaging info available on website

Product data last updated on: Monday, August 7, 2017 - 14:35

#### www.integral-led.com