


Evofire 70mm-100mm cut-out Fire Rated Downlight Round White with Insulation Guard and GU10 Holder

Partcode: ILDLFR70D013 / Page: 1



The Evofire Fire Rated Downlight is a safe and attractive fitting for a GU10 or MR16 LED lamp. The fully open design of the Evofire does not conceal your lamp in a large metal canister, which can trap some of the heat it generates, lowering lamp lifetime and performance. Lamps installed in an Evofire run at up to 10 degrees C cooler than a typical can-style fire rated downlight from leading LED brands - this can extend the lifetime of your lamps.

As well being very tough thanks to its steel construction, The Evofire is also a highly aesthetic choice for Fire Rated lighting. The 1mm blend-in bezel is up to 10 times thinner than typical IP65 rated downlights, has a high quality powder coating and fits almost flush with your ceiling, so the downlight looks discreet and pleasing in any setting.

This downlight is fire rated to 30, 60 and 90 minutes in compliance with BS476 Part 21:1987, Air Tightness compliant with Part C and Part L and Resistance to Sound compliant with Part E. See installation guide for full details.

[Watch Video](#)

Evofire shown with Real Colour GU10 LED lamp (sold separately).

Product Details

Partcode: ILDLFR70D013

Check Code: 668625

Range Name: EVOFIRE

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: Fire Rated

Warranty: 3 Years

CE / RoHS: Yes

Physical Data

Product Finish: Matt white

Material: Steel, Glass

Construction: Pressed Steel, Glass

Partcode: ILDLFR70D013 / Page: 2

Physical Data

Length: 83mm

Diameter: 112mm

Weight (Unpackaged Single Unit): 200g

Cut Out Diameter: 70-100mm

Lamp or Luminaire Shape: Round

Luminaire Fixing: Recess mounted

Fire Rating: 30, 60, 90

Electrical Data

Partcode: ILDLFR70D013 / Page: 3

Environmental

Packaging

EAN Barcode (unit of 1): 5055788236429

Packaged Weight (Unit of 1): 220g

Length (unit of 1): 135mm

Width (unit of 1): 115mm

Depth (unit of 1): 115mm

Outer packaging info available on website

Product data last updated on: Thursday, October 18, 2018 - 13:08