

**EMERGENCY EXIT SIGN 30m VIEWING 4W 3HR MAINTAINED OR
NON-MAINTAINED MANUAL TEST CW UP ARROW INTEGRAL 80 lm**

ILEMES050



The Integral LED Emergency Exit Box brings the efficiency and flexibility of LED to the vital sector of emergency lighting. This self-illuminating exit sign can be clearly seen in emergency situations and has a viewing distance of 30M. At 3.3W maintained and 1.5W in stand-by (non-maintained). This is a Manual Test Version.

Details

Quick Order Code:	335302
Barcode:	5055788254096
Category:	Emergency
Range Name:	Emergency Exit Box
Product Body Finish:	Matt white
Market Segment:	Commercial indoor
Finish:	Matt White
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	300
Product Depth (mm):	40
Product Width (mm):	192
Optic:	Clear Refractor
Material:	Polycarbonate
Bulb or Luminaire Shape:	Rectangle
Luminaire Fixing:	Surface mounted
Placement / Application:	Indoor, Emergency Lighting
Spot Type:	SMD

Electrical Data

Power Consumption (w):	1.5
Input Voltage (V):	220-240
Battery Configuration:	3.2V 1500/3000mAH LIFePO4, 24 hours to charge
Dimming:	Non-Dimmable
Driver Included:	Yes

Electric Current:	AC
Emergency Battery Life (years):	2
Emergency Lumens (lm):	80
Protection Function:	Short circuit, overload and over heating
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	80
Luminous efficacy (lm/W):	53
Correlated Colour Temperature (CCT) (K):	6000
Colour Temperature:	6000K - Cool Daylight
Colour Temperature Name:	Cool Daylight
Colour Rendering Index (CRI):	80
Colour Type:	Single
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	35000
Lighting Method:	Back-lit
Lumens in Emergency mode (lm):	80
Switching Cycles:	15000
Useful Lumens (lm):	100

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Back/Recessed side):	IP20
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	0
Maximum Operating Temperature (°C):	40

Packaging

Package Weight (g):	1000
Package Length (mm):	410
Package Width (mm):	240
Package Depth (mm):	32