

**5W IP65 TWIN SPOT EMERGENCY LUMINAIRE NON MAINTAINED SELF TEST
380LM IK08**

ILEMTS035



Our new comprehensive Twin Spot Emergency Floodlights provide for both indoor offices and retail use with an attractive IP20 model and a more sturdy IP65 option for factories and warehouses.

Details

Quick Order Code:	488872
Barcode:	5055788253853
Category:	Emergency
Range Name:	Twin Spot
Product Body Finish:	White
Market Segment:	Commercial indoor
Finish:	White
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Length (mm):	295
Product Depth (mm):	52
Product Width (mm):	318
Product Weight (g):	850
Optic:	Clear Refractor
Material:	Polycarbonate
Bulb or Luminaire Shape:	Rectangle
Luminaire Fixing:	Wall
Placement / Application:	Indoor, Emergency Lighting
Spot Type:	SMD

Electrical Data

Power Consumption (w):	5
Input Voltage (V):	220-240
Battery Configuration:	3.2V 1500/3000mAH LiFePO4, 24 hours to charge
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC

Emergency Battery Life (years):	2
Emergency Lumens (lm):	500
Protection Function:	Short circuit, overload and over heating
EN:	EN-60608
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	500
Luminous efficacy (lm/W):	100
Correlated Colour Temperature (CCT) (K):	6500
Colour Temperature:	6500K - Cool Daylight
Colour Temperature Name:	Cool Daylight
Colour Rendering Index (CRI):	80
Colour Type:	Single
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	35000
Lighting Method:	Back-lit
Switching Cycles:	15000
Useful Lumens (lm):	400

Environment

EN:	EN-60608
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Back/Recessed side):	IP65
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	0
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	900
Package Length (mm):	420
Package Width (mm):	340
Package Depth (mm):	60