

**200W PRECISION PLUS AREA FLOODLIGHT 26000LM 3000K NON DIM IP66 IK08 5 YR WARRANTY**

ILFLD222



The new high-performance and reliable Precision-Plus Floodlight range is robust, super bright and efficient with brightness levels from 13,000 to 26,000 lumens with up to 130lm/W efficacy. A discreet and sturdy aluminium die-cast housing with good heat dissipation, a toughened glass cover and an IP66 and IK08 rating, makes the floodlights perfect for outdoor industrial, commercial and facade lighting with 60° and asymmetric optics.

**Details**

<b>Quick Order Code:</b>	534458
<b>Barcode:</b>	5055788255079
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Precision Plus
<b>Product Body Finish:</b>	Matt Black
<b>Finish:</b>	Matt Black
<b>Features:</b>	Strong Aluminium body and special paint finish
<b>Warranty (Years):</b>	5
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	432
<b>Product Depth (mm):</b>	60
<b>Product Width (mm):</b>	330
<b>Product Weight (g):</b>	6000
<b>Optic:</b>	Clear Refractor
<b>Material:</b>	Aluminium, Polycarbonate, Tempered glass
<b>Construction:</b>	Die Cast Aluminium
<b>Bulb or Luminaire Shape:</b>	Rectangle
<b>Luminaire Fixing:</b>	Wall
<b>Placement / Application:</b>	Outdoor, General Lighting
<b>Spot Type:</b>	SMD

**Electrical Data**

<b>Power Consumption (w):</b>	200
<b>Power Factor:</b>	0.9



<b>Input Voltage (V):</b>	220-240
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>Protection Function:</b>	Short circuit, overload and over heating
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	26000
<b>Luminous efficacy (lm/W):</b>	130
<b>Correlated Colour Temperature (CCT) (K):</b>	3000
<b>Colour Temperature:</b>	3000K - Warm White
<b>Colour Temperature Name:</b>	Warm White
<b>Beam Angle:</b>	120
<b>Colour Rendering Index (CRI):</b>	80
<b>Colour Type:</b>	Single
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Size (mm):</b>	2835
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	50000
<b>Lighting Method:</b>	Back-lit
<b>Switching Cycles:</b>	15000
<b>Useful Lumens (lm):</b>	400

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>New Energy Rating:</b>	D
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK08
<b>IP Rating (Back/Recessed side):</b>	IP66
<b>IP Rating (Ingress Protection):</b>	IP66
<b>Lowest Operating Temperature (°C):</b>	-30
<b>Maximum Operating Temperature (°C):</b>	45



## Packaging

Package Weight (g):	7300
Package Length (mm):	510
Package Width (mm):	430
Package Depth (mm):	130

[Portal.integral-led.com](http://Portal.integral-led.com)