

**GLS BULB E27 470LM 4.8W 5000K NON-DIMM 240 BEAM FROSTED INTEGRAL**

ILGLSE27NF111



This 4.8W great all-purpose retrofit Integral LED Classic Globe (GLS) delivers a daylight output equivalent to 40W, offering big energy savings over equivalent incandescent bulbs. With a 470 lumen output and frosted finish this lamp is ideal for rooms with a single pendant fitting, living rooms, hallways and kitchens.

**Details**

<b>Quick Order Code:</b>	630840
<b>Barcode:</b>	5055788258926
<b>Category:</b>	Lamps
<b>Range Name:</b>	Everyday
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial indoor, Residential indoor
<b>Warranty (Years):</b>	2
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	103
<b>Product Width (mm):</b>	60
<b>Product Weight (g):</b>	30
<b>Material:</b>	Plastic
<b>Base Term:</b>	Edison screw
<b>Bulb Base:</b>	E27
<b>Construction:</b>	Plastic
<b>Globe Finish:</b>	Frosted
<b>Globe Type:</b>	GLS
<b>Bulb or Luminaire Shape:</b>	Round
<b>Placement / Application:</b>	Indoor, General Lighting
<b>Spot Type:</b>	SMD

**Electrical Data**

<b>Power Consumption (w):</b>	4.8
<b>Power Factor:</b>	0.4
<b>Wattage equivalent (W):</b>	40
<b>Amperage (mA):</b>	42



<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>True Wattage Eq (W):</b>	40
<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	470
<b>Luminous efficacy (lm/W):</b>	98
<b>Correlated Colour Temperature (CCT) (K):</b>	5000
<b>Colour Temperature:</b>	5000K - Daylight
<b>Colour Temperature Name:</b>	Daylight
<b>Beam Angle:</b>	240
<b>Colour Rendering Index (CRI):</b>	80
<b>Colour Type:</b>	Single
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	15000
<b>Switching Cycles:</b>	7500

## Environment

<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Previous Energy Rating:</b>	A+
<b>New Energy Rating:</b>	F
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	40



## Packaging

[Portal.integral-led.com](http://Portal.integral-led.com)

<b>Package Weight (g):</b>	60
<b>Package Length (mm):</b>	120
<b>Package Width (mm):</b>	65
<b>Package Depth (mm):</b>	65