

## **Product Specification Sheet**

### GU10 PAR16 7W (65W) 2700K 520Im Dimmable Lamp 55 deg Beam Angle

Partcode: ILGU10DC100 / Page: 1



This GU10 lamp offers a wider beam angle of 55 degrees, which will cover a larger area in light with fewer lamps than other GU10 spotlights. The LEDs are specially arranged for a COB-like effect, which paired with the diffuser lens creates a light quality very similar to traditional halogen spotlights.

#### **Product Details**

Partcode: ILGU10DC100

Check Code: 368334 Range Name: Classic

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: GU10 Warranty: 2 Years CE / RoHS: Yes

#### **Physical Data**

Base Type: GU10

Base Colour: Matt white Product Finish: Matt white

Spot Type: SMD with "COB like effect"
Optic: Designed to give a Classic Look

Material: Plastic and Aluminium heat-sink, Injection moulded diffuser

Construction: Plastic White and "Classic look" difuser lens



# **Product Specification Sheet**

Partcode: ILGU10DC100 / Page: 2

### **Physical Data**

Length: 54mm Width: 50mm

Weight (Unpackaged Single Unit): 50g Lamp or Luminaire Shape: Round

Lamp Fixing: Downlight

#### **Electrical Data**

Voltage Range: 220-240V

Power Consumption: 7.0 Watts

Driver included: Yes Electric Current: AC Ampage: 34.00mA

Frequency Range: 50/60 Hz

Power Factor: >=0.80

Wattage Equivalent: 65 Watts

Dimming: Dimmable LVD Certified: Yes EN: EN-62560

#### **Light Data**

Useful Lumens: 460lm (Rated luminous flux in a 90° cone)

Lumens: 520lm

Lumens per Watt: 74.0lm/W

Peak Intensity: 550Cd Beam Angle: 55°

Correlated Colour Temperature (CCT): 2,700k

Colour Temperature: Warm

Colour Rendering Index (CRI): >=80

LED Type: Surface mounted device (SMD)

LED Size: 2835

Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs


Switching Cycles: >7,500 X



# **Product Specification Sheet**

Partcode: ILGU10DC100 / Page: 3

#### **Environmental**



Energy Rating: A+

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP20

Hg 0% (Mercury Free): Yes

### **Packaging**



EAN Barcode (unit of 1): 5055788237181

Outer packaging info available on website

Product data last updated on: Tuesday, August 28, 2018 - 17:16