

GU10 BULB 190LM 2.5W 2700K NON-DIMM 36 BEAM INTEGRAL

ILGU10NC128



The Integral LED Low Energy GU10 range provides a mellow smoothing light. By incorporating a stylish engineered lens in an affordable GU10, the lamp offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED. Idea for porches and other areas where low lighting is specified.

Details

Quick Order Code:	303893
Barcode:	5055788267157
Category:	Lamps
Range Name:	Single Colour
Product Body Finish:	White
Market Segment:	Decorative indoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	56
Product Width (mm):	50
Product Weight (g):	25
Optic:	Designed to give a Classic Look
Material:	Plastic and Aluminium heat-sink, Injection moulded diffuser
Base Term:	GU10
Bulb Base:	G4
Construction:	Plastic White and "Classic look" difuser lens
Globe Finish:	White
Bulb or Luminaire Shape:	Round
Placement / Application:	Decorative indoor
Spot Type:	SMD

Electrical Data

Power Consumption (w):	2.5
Power Factor:	0.5
Wattage equivalent (W):	20

Amperage (mA):	20
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
True Wattage Eq (W):	20
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	190
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature:	2700K - Warm
Colour Temperature Name:	Warm
Beam Angle:	36
Colour Rendering Index (CRI):	80
Colour Type:	Single
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
New Energy Rating:	G
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Packaging

Package Weight (g):

39

Portal.integral-led.com

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Length (mm):	62
Package Width (mm):	48
Package Depth (mm):	48