

Product Specification Sheet

GU10 Classic PAR16 5.7W (68W) 4000K 530lm Non-Dimmable Lamp - 10 Pack

Partcode: ILGU10NE071-10 / Page: 1



The Integral LED Classic GU10 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable GU10, the Classic offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

Product Details

Partcode: ILGU10NE071-10

Check Code: 369715 Range Name: Classic

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: GU10 Warranty: 2 Years CE / RoHS: Yes

Physical Data

Lamp Base: GU10 PAR16

Base Type: GU10

Base Colour: Matt white Globe Finish: Clear

Product Finish: Matt white

Spot Type: SMD with "COB like effect"
Optic: Designed to give a Classic look

Material: Plastic and Aluminium heat-sink, Injection moulded diffuser

Construction: Plastic White and "Classic look" difuser lens



Product Specification Sheet

Partcode: ILGU10NE071-10 / Page: 2

Physical Data

Length: 54mm Width: 50mm

Lamp or Luminaire Shape: Round

Lamp Fixing: Downlight

Electrical Data

Voltage Range: 220-240V

Power Consumption: 5.7 Watts

Driver included: Yes

Driver IC Manufacturer: Silan Microelectronics

Electric Current: AC Ampage: 46.00mA

Frequency Range: 50 Hz Power Factor: >=0.50

Wattage Equivalent: 68 Watts

Dimming: Non-dimmable

LVD Certified: Yes EN: EN-62560

Light Data

Useful Lumens: 480lm (Rated luminous flux in a 90° cone)

Lumens: 530lm

Lumens per Watt: 93.0lm/W

Peak Intensity: 900Cd Beam Angle: 36°

Correlated Colour Temperature (CCT): 4,000k

Colour Temperature: Cool White
Colour Rendering Index (CRI): >=80

LED Type: Surface mounted device (SMD)

LED Size: 3030

Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs


Switching Cycles: >7,500 X



Product Specification Sheet

Partcode: ILGU10NE071-10 / Page: 3

Environmental



Energy Rating: A+

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788222194

Outer packaging info available on website

Product data last updated on: Monday, August 7, 2017 - 14:33