

**TOUGHSHELL CIRCULAR HIGH BAY 1PK IP65 19500LM 150W 4000K 60
BEAM 1-10V DIMMABLE INTEGRAL**

ILHBC164



The Tough-Shell Circular High Bay is a rugged, attractive and highly efficient solution for lighting large indoor facilities such as warehouses, production facilities and indoor sports halls. Running at an efficacy of 130lm/W, this Tough-Shell provides 19,500lm and thanks to its skilfully engineered aluminium body it effectively dissipates heat while maintaining IK10 impact resistance.

Details

Quick Order Code:	100973
Barcode:	5055788239413
Category:	Luminaires
Range Name:	Tough-Shell
Type:	Circular
Product Type:	Circular High Bay
Product Body Finish:	Matt Black
Market Segment:	Commercial indoor and outdoor, Industrial indoor and outdoor
Finish:	Matt Black
Warranty (Years):	5
CE RoHS:	Yes

Physical Data

Product Length (mm):	139
Product Weight (g):	5600
Optic:	Polycarbonate diffuser
Material:	Aluminium, Polycarbonate
Construction:	Aluminium heat-sink, PC injection moulded driver case
Bulb or Luminaire Shape:	Round
Luminaire Fixing:	Suspended
Mounting Type:	Rear Cable Entry
Placement / Application:	Indoor, Outdoor, General Lighting
Typical Mounting Height:	4M+

Electrical Data

Power Consumption (w):	150
-------------------------------	-----


Power Factor:	0.95
Input Voltage (V):	220-240
Dimming:	Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-60598, EN61000, EN61547, EN55015, IEC62321
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	19500
Luminous efficacy (lm/W):	130
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature Name:	Cool White
Beam Angle:	60
Colour Rendering Index (CRI):	70
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	50000
Switching Cycles:	25000
Useful Lumens (lm):	19500

Environment

EN:	EN-60598, EN61000, EN61547, EN55015, IEC62321
LVD Certified:	Yes
CE RoHS:	Yes
EU Luminaire:	L
Hg 0% (Mercury Free):	Yes
IK Rating (Impact Protection):	IK10
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	-30
Maximum Operating Temperature (°C):	45
Metal Halide Equivalent:	250



Portal.integral-led.com

Packaging

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Weight (g):	6600
Package Length (mm):	445
Package Width (mm):	225
Package Depth (mm):	445