

Tough-Shell High Bay 26000lm 200W 4000K Dimmable 60 deg Beam Angle Dimmable with Integrated Emergency Function

Partcode: ILHBC168E / Page: 1



The Tough-Shell Circular High Bay is a rugged, attractive and highly efficient solution for lighting large indoor facilities such as warehouses, production facilities and indoor sports halls. Running at an efficacy of 130lm/W, this Tough-Shell provides up to 26,000lm and thanks to its skilfully engineered aluminium body it effectively dissipates heat while maintaining IK10 impact resistance.

This emergency model will provide 2600lm for 3 hours in the event of a power cut.

Product Details

Partcode: ILHBC168E

Check Code: 522074

Range Name: Tough-Shell

Product Type: Circular High Bay

Warranty: 5 Years

CE / RoHS: Yes

Physical Data

Product Finish: Matt Black

Optic: Polycarbonate diffuser

Material: Aluminium, Polycarbonate

Construction: Aluminium heat-sink, PC injection moulded driver case

Physical Data

Length: 139mm
Width: 360mm
Depth: 139mm
Diameter: 360mm
Weight (Unpackaged Single Unit): 6500g
Lamp or Luminaire Shape: Round
Luminaire Fixing: Suspended


Electrical Data

Voltage Range: 100-240V
Power Consumption: 200.0 Watts
Driver included: Yes
Electric Current: AC
Frequency Range: 50/60 Hz
Power Factor: ≥ 0.95
Dimming: Dimmable
LVD Certified: Yes
EN: EN-60598, EN61000, EN61547, EN55015, IEC62321

Light Data

Useful Lumens: 26000lm (Rated luminous flux in a 90° cone)
Lumens: 26,000lm
Lumens per Watt: 130.0lm/W
Beam Angle: 60°
Correlated Colour Temperature (CCT): 4000k
Colour Temperature: Cool White
Colour Rendering Index (CRI): ≥ 73
LED Type: Surface mounted device (SMD)
Instant on - Less than 1 second: Yes
Lifetime: 50,000 hrs
Switching Cycles: $>25,000$ X

Environmental



Lowest Operating Temperature: 0 degrees

Maximum Operating Temperature: 45 degrees

IK (Impact Protection) Rating: 10

IP (Ingress Protection) Rating: IP40

Hg 0% (Mercury Free): Yes

Packaging

EAN Barcode (unit of 1): 5055788246268

Packaged Weight (Unit of 1): 8,200g

Length (unit of 1): 445mm

Width (unit of 1): 225mm

Depth (unit of 1): 445mm

Outer packaging info available on website

Product data last updated on: Monday, June 22, 2020 - 15:15