Partcode: ILHBL204 / Page: 1

# Slimline Linear High Bay 200W 26000lm 4000K 120 deg Beam Angle Dimmable

Image: Second secon

Discreet and attractive, the Slimline Linear High Bay is a functional and aesthetic choice for large showrooms and retail premises as well as industrial environments. This High Bay offers 26,000 lumen output at a super-efficient 130lm/W, which will make huge savings to energy costs compared to legacy lighting technology. The IP65 rating makes it water, steam and dust resistant, ensuring that it is suitable for demanding industrial workplaces.

## **Product Details**

Partcode: ILHBL204 Check Code: 818271 Range Name: Slimline Product Type: Linear High Bay Warranty: 5 Years CE / RoHS: Yes

# **Physical Data**

Optic: Polycarbonate diffuser Material: PC Construction: PC extrusion

## www.integral-led.com

Partcode: ILHBL204 / Page: 2

#### **Physical Data**

Length: 1 205mm Width: 135mm Depth: 72mm Weight (Unpackaged Single Unit): 6600g Lamp or Luminaire Shape: Linear Luminaire Fixing: Suspended

#### **Electrical Data**

Voltage Range: 100-240V Power Consumption: 200.0 Watts Driver included: Yes Electric Current: AC Frequency Range: 50/60 Hz Hz Power Factor: >=0.95 Dimming: Dimmable Protection Function: Short Circuit, overload and overheating protection on driver LVD Certified: Yes EN: EN-60598

## **Light Data**


Useful Lumens: 26000lm (Rated luminous flux in a 90° cone) Lumens: 26,000lm Lumens per Watt: 130.0lm/W Beam Angle: 120° Correlated Colour Temperature (CCT): 4000k Colour Temperature: Cool White Colour Rendering Index (CRI): >=70 LED Type: Surface mounted device (SMD) LED Size: 3030 Instant on - Less than 1 second: Yes Lifetime: 50,000 hrs Switching Cycles: >100,000 X

## www.integral-led.com



Partcode: ILHBL204 / Page: 3

#### **Environmental**



Lowest Operating Temperature: -30 degrees Maximum Operating Temperature: 50 degrees IK (Impact Protection) Rating: 10 IP (Ingress Protection) Rating: IP65 Hg 0% (Mercury Free): Yes

#### **Packaging**

EAN Barcode (unit of 1): 5055788246510 Packaged Weight (Unit of 1): 8,400g Length (unit of 1): 1,260mm Width (unit of 1): 180mm Depth (unit of 1): 90mm **Outer packaging info available on website** 

Product data last updated on: Monday, April 8, 2019 - 10:35

#### www.integral-led.com