IP65 PAR38 15W (135W) Amber Colour Non-Dimmable Lamp

Partcode: ILPAR38NK011 / Page: 1



Integral LED IP65-rated PAR lamps have been designed for use in outdoor areas such as gardens, country parks, and estates where you can illuminate flowerbeds, trees, statues and walls for example, creating beautiful feature points. The lamps are available in a selection of colours, as well as a high CRI warm white.

Please note: This IP65 PAR38 is only for use in suitably rated outdoor fittings and sockets.

Product Details

Partcode: ILPAR38NK011 Check Code: 023023 Product Type: PAR Warranty: 2 Years CE / RoHS: Yes

Physical Data

Lamp Base: E27 Base Type: Edison screw Base Colour: White Globe Type: PAR38 Globe Finish: Clear Product Finish: Matt white Spot Type: COB Optic: Refractor Cover for enhanced light distribution Material: Aluminium, Polycarbonate Construction: Plastic and Aluminium heat-sink, PMMA diffuser

www.integral-led.com

integral LED

Partcode: ILPAR38NK011 / Page: 2

Physical Data

Length: 128mm Diameter: 120mm Weight (Unpackaged Single Unit): 230g Lamp Fixing: Downlight

Electrical Data

Voltage Range: 100-240V Power Consumption: 15.0 Watts Driver included: Yes Electric Current: AC Ampage: 67.00mA Frequency Range: 50/60 Hz Power Factor: >=0.90 Wattage Equivalent: 135 Watts Dimming: Non-dimmable LVD Certified: Yes EN: EN-62560

Light Data

Beam Angle: 36° Colour Temperature: Amber Colour Type: Single LED Type: Chip-on-board (COB) Instant on - Less than 1 second: Yes Lifetime: 25,000 hrs Switching Cycles: >12,500 X

www.integral-led.com



Partcode: ILPAR38NK011 / Page: 3

Environmental

Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP65 Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788227342 Packaged Weight (Unit of 1): 320g Length (unit of 1): 125mm Width (unit of 1): 125mm Depth (unit of 1): 145mm **Outer packaging info available on website**

Product data last updated on: Monday, August 7, 2017 - 14:36

www.integral-led.com