

PRODUCT

PATCO

Pattress for use with Mains Carbon Monoxide Alarms

DESCRIPTION

Pattress for surface installation of all Kidde carbon monoxide alarms



KEY FEATURES

- Surface mounted fits all Kidde mains CO alarms 4MCO and 4MDCO
- Easy to fit for convenient installation, particularly suitable for retrofit

WHERE TO USE

For surface installations involving cable entry via trunking or conduit. The PATCO can be used, via a suitable relay control, to trigger auxiliary devices such as door closers, warning lights, horns and suitable warden-call systems. This pattress is fully compatible with the Kidde 4MCO and 4MDCO mains carbon monoxide alarms.

GENERAL FEATURES

Model	PATCO	
Power Supply	230V mains-powered	
Temperature Range	0°C to + 40°C Up to 93% Relative Humidity (RH) non-condensing	
Humidity Range		
Pattress Dimensions	130 x 130 x 20mm / 130 x 130 x 20mm	
Pattress Weight	120g / 120g	
Warranty	6 years	
Approvals	CE tested and certified	

OPTIONAL PRODUCT

For installers of Firex mains alarms the following Firex-specific pattress may be used:

SMK4896 For surface installations involving cable entry via trunking or conduit with loose-fit terminal block for ease of installation

For further information see SMK4896 datasheet.

For more information or to contact Kidde Sales:

01753 766 392 kiddesafetyeurope.co.uk

PRODUCT

PATCO

Pattress for use with Mains Carbon Monoxide Alarms

DESCRIPTION

Pattress for surface installation of all Kidde carbon monoxide alarms



NOTES	

PACKAGED SPECIFICATIONS

	PLAIN BOX	
Order Code	PATCO	
Pack Dimensions	135 x 135 x 22mm	
Pack Weight	125g	
UPC Barcode	0-254177-230009	
Case Quantity	6	
Case Dimensions	145 x 145 x 150mm	
Case Weight	0.8Kg	
ITF Outer Code	n/a	