Xnightsbridge

DATASHEET



12DC40

IP20 12V DC 40W LED Driver - Constant Voltage

www.mlaccessories.co.uk

DESCRIPTION IP20 12V DC 40W LED Driver - Constant Voltage 0.14 FINISH White Length - 166 Height - 24 Width - 52 CONSTRUCTION CONSTRUCTI	MLA PART CODE	12DC40
White	DESCRIPTION	IP20 12V DC 40W LED Driver - Constant Voltage
DIMENSIONS (MM) Length - 166 Height - 24 Width - 52 CONSTRUCTION Construction - Polycarbonate CLASS II IP RATING DISPLACEMENT FACTOR SVM O PST-LM 0 LIFE SPAN (HRS) DIMMABLE NO INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIVER DRIVER Length - 166 Height - 24 Width - 52 Construction - Polycarbonate IP 20 DOUBLED O DISPLACEMENT FACTOR SOUP O DISPLACEMENT FACTOR SOUP O DISPLACEMENT FACTOR O D D D D D D D D D D D D	NET WEIGHT (KG)	0.14
DIMENSIONS (MM)	FINISH	White
I	DIMENSIONS (MM)	Height - 24
IP RATING DISPLACEMENT FACTOR >0.9 SVM 0 PST-LM 0 LIFE SPAN (HRS) DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER DRIV	CONSTRUCTION	Construction - Polycarbonate
DISPLACEMENT FACTOR SVM 0 PST-LM 0 LIFE SPAN (HRS) 50,000 DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	CLASS	II
SVM 0	IP RATING	IP20
DRIVER PST-LM 0 LIFE SPAN (HRS) 50,000 No INPUT VOLTAGE SECONDARY VOLTAGE 12V DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	DISPLACEMENT FACTOR	>0.9
LIFE SPAN (HRS) DIMMABLE No INPUT VOLTAGE SECONDARY VOLTAGE DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	SVM	0
DIMMABLE INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE 12V DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	PST-LM	0
INPUT VOLTAGE SECONDARY VOLTAGE 12V DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	LIFE SPAN (HRS)	50,000
DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	DIMMABLE	No
DRIVER TYPE - Constant Voltage MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	INPUT VOLTAGE	230V 50Hz
MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)20~50°C	SECONDARY VOLTAGE	12V
OAGE TEMPETATIONE (10) - 00 0	DRIVER	MAX. OUTPUT - 40W OUTPUT VOLTAGE - 12V OUTPUT CURRENT - 0 - 3300mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 85 ISOLATION - SELV
WARRANTY 1year(s)	WARRANTY	1year(s)
MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493	MANUFACTURED IN ACCORDANCE WITH	EN 61347, EN 62493
ORIGIN OF MANUFACTURE China	ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN 5055832991656	EAN	5055832991656

Date Created: 27/07/2022 16:34



