


DATASHEET



BT9ACTS

230V IP65 9W CCT Adjustable LED Bulkhead with Sensor

www.mlaccessories.co.uk



MLA PART CODE	BT9ACTS
DESCRIPTION	230V IP65 9W CCT Adjustable LED Bulkhead with Sensor
NET WEIGHT (KG)	0.64
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 256 Projection - 74
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	9
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	730 / 810 / 780
LUMENS LIGHT SOURCE ONLY (LM)	900
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	118.41
CIRCUIT WATTAGE (W)	7.617
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.036
DISPLACEMENT FACTOR	>0.9
SVM	0.536
PST-LM	0.025
BEAM ANGLE (DEGREES)	115
LIFE SPAN (HRS)	30,000

L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 8.6W OUTPUT VOLTAGE - 30 - 43V OUTPUT CURRENT - 200mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 80 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
SENSOR TYPE	Microwave
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	150
OPTIMUM DETECTION RANGE (M)	1m ~ 6m ceiling mounted @ 3m; 2m ~ 18m wall mounted @ 2m; mounting height 6m max.
SENSOR DURATION	5 seconds - 30 minutes
SENSOR LUX SETTINGS	2 lux - 50 lux / Disable
STANDBY POWER	<0.5W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270825343

Date Created: 05/08/2022 16:53

