


DATASHEET



CPL24CT

230V 24W CCT Adj Circular LED Panel- 290mm

www.mlaccessories.co.uk



MLA PART CODE	CPL24CT
DESCRIPTION	230V 24W CCT Adj Circular LED Panel- 290mm
NET WEIGHT (KG)	0.64
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 290 Projection - 15 Base Diameter - 246 Minimum Void - 50
CUT-OUT (MM)	Min./Max. Cut-out - 55 - 250
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	24
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1940/2140/2100
LUMENS LIGHT SOURCE ONLY (LM)	3050
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	129.9
LUMENS EMERGENCY MODE (LM)	640/710/680
CIRCUIT WATTAGE (W)	23.5
CCT	3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.116
DISPLACEMENT FACTOR	>0.7
SVM	0.249
PST-LM	0.26

BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
IC RATED	Yes
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832984184

Date Created: 29/07/2022 16:20

