Xnightsbridge

DATASHEET



EMRNSTL

230V 4W LED Emergency Exit Sign - Self-test

www.mlaccessories.co.uk

MLA PART CODE	EMRNSTL
DESCRIPTION	230V 4W LED Emergency Exit Sign - Self-test
NET WEIGHT (KG)	0.57
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 324 Height - 169 Projection - 42
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	4
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	150
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	36.71
LUMENS EMERGENCY MODE (LM)	120
CIRCUIT WATTAGE (W)	4.08
ССТ	6000K
LIGHT COLOUR	Daylight
CRI	>80
RUNNING CURRENT (A)	0.033
SVM	0.04
BEAM ANGLE (DEGREES)	110
LIFE SPAN (HRS)	30,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes
OPERATING TEMPERATURE	0~45°C





Xnightsbridge

INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	2 x 20
CABLE GLAND INCLUDED	No
BATTERY INCLUDED	Yes
WARRANTY	3year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270834987

Date Created: 31/01/2024 13:07





