Xnightsbridge


DATASHEET



LDGL5

230V IP65 5W LED Stainless Steel Recessed Ground Light 3000K

www.mlaccessories.co.uk



MLA PART CODE	LDGL5
DESCRIPTION	230V IP65 5W LED Stainless Steel Recessed Ground Light 3000K
NET WEIGHT (KG)	0.58
FINISH	Stainless Steel
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 68 Projection - 4 Recessed Depth - 80
CUT-OUT (MM)	Cut-out Diameter - 55 Cut-out with Sleeve - 60
CONSTRUCTION	Construction - 304 Stainless steel
CLASS	
IP RATING	IP65
WATTAGE (W)	5
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	240
LUMENS LIGHT SOURCE ONLY (LM)	430
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	86.69
CIRCUIT WATTAGE (W)	5
ССТ	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.03
DISPLACEMENT FACTOR	>0.9
SVM	0.003
PST-LM	0.65





Xnightsbridge

	=0
BEAM ANGLE (DEGREES)	50
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
MAX. WEIGHT LOADING	800kg at 5mph
OPERATING TEMPERATURE	-25~35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	2
CABLE TYPE	3-core 1.00mm ² H05RN-F
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270800364
D 1 0 1 1 00/00/0000 15 10	

Date Created: 08/08/2022 15:46





