
Xnightsbridge

DATASHEET



LWALL3A 230V IP65 3W LED Adjustable Wall Light

www.mlaccessories.co.uk



| MLA PART CODE | LWALL3A |
|-------------------------------|--|
| DESCRIPTION | 230V IP65 3W LED Adjustable Wall Light |
| NET WEIGHT (KG) | 0.395 |
| FINISH | Brushed Chrome |
| DIFFUSER | Clear |
| DIMENSIONS (MM) | Diameter - 49 Height - 66 Projection - 139 Base Diameter - 62 Base Height - 25 |
| CONSTRUCTION | Construction - Aluminium |
| CLASS | I |
| IP RATING | IP65 |
| WATTAGE (W) | 4 |
| LAMP TECHNOLOGY | CoB LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 175 |
| LUMENS LIGHT SOURCE ONLY (LM) | 285 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 73.07 |
| CIRCUIT WATTAGE (W) | 3.9 |
| ССТ | 3000K |
| LIGHT COLOUR | Warm White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.039 |
| SVM | 0.007 |
| PST-LM | 0.57 |
| BEAM ANGLE (DEGREES) | 65 |
| LIFE SPAN (HRS) | 30,000 |





Xnightsbridge

| L70B50 LIFESPAN (HRS) | 50,000 |
|--|---|
| DIMMABLE | No |
| OPERATING TEMPERATURE | -25~35°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Blind grommet |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 3W OUTPUT VOLTAGE - 5-10V OUTPUT CURRENT - 300mA POWER FACTOR - >0.4 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 85°C |
| WARRANTY | 2year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270811186 |

Date Created: 09/08/2022 10:23





