Xnightsbridge


DATASHEET



MLRCTM2

230V IP44 10W 500 x 390mm LED Mirror with Dual Shaver Socket

www.mlaccessories.co.uk



MLA PART CODE	MLRCTM2
DESCRIPTION	230V IP44 10W 500 x 390mm LED Mirror with Dual Shaver Socket
NET WEIGHT (KG)	5.55
DIMENSIONS (MM)	Height - 500 Width - 390 Projection - 60 Base Width - 350 Base Height - 480 Base Depth - 55
CONSTRUCTION	Construction - Pressed steel Construction 2 - & glass
CLASS	I
IP RATING	IP44
WATTAGE (W)	10
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	130
LUMENS LIGHT SOURCE ONLY (LM)	1395
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	138.2
CIRCUIT WATTAGE (W)	10.09
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.057
DISPLACEMENT FACTOR	>0.7
SVM	0.008
PST-LM	0.012
BEAM ANGLE (DEGREES)	140





Xnightsbridge

L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
OPERATING TEMPERATURE	40°C
INPUT VOLTAGE	230V 50Hz
SECONDARY VOLTAGE	110/230V
LOAD/MAX. LOAD	20VA
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 12.6W OUTPUT VOLTAGE - 24-42V OUTPUT CURRENT - 300mA POWER FACTOR - 0.85 EFFICIENCY FULL LOAD - 83 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	1year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270864625

Date Created: 03/08/2022 13:07





