


DATASHEET



MRBLED

230V IP20 32W LED CAT2 Recessed Modular Fitting
600x600mm 4000K

www.mlaccessories.co.uk



MLA PART CODE	MRBLED
DESCRIPTION	230V IP20 32W LED CAT2 Recessed Modular Fitting 600x600mm 4000K
NET WEIGHT (KG)	3.145
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Length - 595 Width - 595 Depth - 52 Recessed Depth - 52
CONSTRUCTION	Construction - Steel
CLASS	I
IP RATING	IP20
WATTAGE (W)	32
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3370
LUMENS LIGHT SOURCE ONLY (LM)	3805
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	114.756
CIRCUIT WATTAGE (W)	33.2
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.153
DISPLACEMENT FACTOR	>0.9
SVM	0.849
PST-LM	0.04
BEAM ANGLE (DEGREES)	105

LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
EMERGENCY CONVERSION KIT	EMKIT2
IC RATED	No
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 45W OUTPUT CURRENT - 1050mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 91 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 70°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832931652

Date Created: 03/08/2022 14:23

