Xnightsbridge

DATASHEET




TPB14EMSLED

230V IP44 14W LED Emergency Bulkhead Fitting

with Sensor 6000K

www.mlaccessories.co.uk



| MLA PART CODE | TPB14EMSLED |
|-------------------------------|--|
| DESCRIPTION | 230V IP44 14W LED Emergency Bulkhead Fitting with Sensor 6000K |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 330 Projection - 110 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | II |
| IP RATING | IP44 |
| WATTAGE (W) | 14 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1070 |
| LUMENS LIGHT SOURCE ONLY (LM) | 1490 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 74.8 |
| LUMENS EMERGENCY MODE (LM) | 300 |
| CIRCUIT WATTAGE (W) | 14.3 |
| CCT | 6000K |
| LIGHT COLOUR | Daylight |
| CRI | >80 |
| RUNNING CURRENT (A) | 0.065 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.001 |
| PST-LM | 0.03 |
| BEAM ANGLE (DEGREES) | 105 |
| LIFE SPAN (HRS) | 30,000 |
| L70B50 LIFESPAN (HRS) | 72,000 |
| DIMMABLE | No |





Xnightsbridge

| EMERGENCY | Maintained / Non-maintained / Switched |
|--|---|
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 24-28V OUTPUT CURRENT - 500mA POWER FACTOR - 0.9 CASE TEMPERATURE (Tc) - 50°C |
| SENSOR TYPE | Microwave |
| OPTIMUM DETECTION RANGE (M) | 2 - 8m |
| SENSOR DURATION | 10s - 30min |
| SENSOR LUX SETTINGS | 10 - 2000 lux |
| BATTERY INCLUDED | Yes |
| STANDBY POWER | 0.17W |
| WARRANTY | 3year(s) |
| WARRANTY INFORMATION | (excluding battery) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055559190103 |

Date Created: 05/08/2022 15:48





