Xnightsbridge

DATASHEET




TPB14LEDA

230V IP44 14W LED Bulkhead with Sensor/Dimming

Function 6000K

www.mlaccessories.co.uk



MLA PART CODE	TPB14LEDA
DESCRIPTION	230V IP44 14W LED Bulkhead with Sensor/Dimming Function 6000K
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 330 Projection - 110
CONSTRUCTION	Construction - Polycarbonate
CLASS	ll l
IP RATING	IP44
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1070
LUMENS LIGHT SOURCE ONLY (LM)	1490
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	74.8
CIRCUIT WATTAGE (W)	14.3
ССТ	6000K
LIGHT COLOUR	Daylight
CRI	>80
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.03
BEAM ANGLE (DEGREES)	105
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	72,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C





Xnightsbridge

INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 24-28V OUTPUT CURRENT - 500mA POWER FACTOR - 0.5 CASE TEMPERATURE (Tc) - 65°C
SENSOR TYPE	Microwave - Corridor Function
OPTIMUM DETECTION RANGE (M)	2m~8m @ 2.5m height
SENSOR DURATION	10sec - 12min
SENSOR LUX SETTINGS	10lx - daylight
STANDBY POWER	0.17W
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832944829

Date Created: 05/08/2022 15:52





