Xnightsbridge


DATASHEET



TPB14SLED

230V IP44 14W LED Bulkhead with Sensor 6000K

www.mlaccessories.co.uk



MLA PART CODE	TPB14SLED
DESCRIPTION	230V IP44 14W LED Bulkhead with Sensor 6000K
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 330 Projection - 110
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP44
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1070
LUMENS LIGHT SOURCE ONLY (LM)	1490
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	74.8
CIRCUIT WATTAGE (W)	14.3
ССТ	6000K
LIGHT COLOUR	Daylight
CRI	>80
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.03
BEAM ANGLE (DEGREES)	105
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	72,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C





Xnightsbridge

INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 24-28V OUTPUT CURRENT - 500mA POWER FACTOR - 0.9 CASE TEMPERATURE (Tc) - 50°C
SENSOR TYPE	Microwave
OPTIMUM DETECTION RANGE (M)	2 - 8m
SENSOR DURATION	10s - 30min
SENSOR LUX SETTINGS	10 - 2000 lux
STANDBY POWER	0.17W
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055559190127

Date Created: 05/08/2022 15:55





