


DATASHEET



TPR14LEDA

230V IP65 14W LED Bulkhead with Sensor/Dimming Function 4000K

www.mlaccessories.co.uk



MLA PART CODE	TPR14LEDA
DESCRIPTION	230V IP65 14W LED Bulkhead with Sensor/Dimming Function 4000K
NET WEIGHT (KG)	0.65
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 285 Projection - 86
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	1100
LUMENS LIGHT SOURCE ONLY (LM)	1475
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	105.4
CIRCUIT WATTAGE (W)	14
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.065
DISPLACEMENT FACTOR	>0.9
SVM	0.001
PST-LM	0.027
BEAM ANGLE (DEGREES)	115
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	60,000

DIMMABLE	No
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 24-28V OUTPUT CURRENT - 500mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 83.6 CASE TEMPERATURE (Tc) - 50°C
SENSOR TYPE	Microwave - Corridor Function
OPTIMUM DETECTION RANGE (M)	2 - 8m @2.5m
SENSOR DURATION	10s - 12min
SENSOR LUX SETTINGS	10 - 50 lux / 24h
STANDBY POWER	0.16W
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832937166

Date Created: 05/08/2022 15:51

