


DATASHEET



TRLED15D

230V IP65 5ft 29W Single LED Non-Corrosive - 6000K

www.mlaccessories.co.uk



MLA PART CODE	TRLED15D
DESCRIPTION	230V IP65 5ft 29W Single LED Non-Corrosive - 6000K
NET WEIGHT (KG)	2
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Height - 90 Width - 94
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	29
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3610
LUMENS LIGHT SOURCE ONLY (LM)	4070
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	142.32
CIRCUIT WATTAGE (W)	28.65
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.129
DISPLACEMENT FACTOR	>0.9
SVM	0.782
PST-LM	0.043
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000

DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30W EFFICIENCY FULL LOAD - 89.11% ISOLATION - SELV
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832988564

Date Created: 06/07/2022 14:40

