



DATASHEET



TRLED25EMD

230V IP65 5ft 50W Twin LED Non-Corrosive
Emergency - 6000K

www.mlaccessories.co.uk



MLA PART CODE	TRLED25EMD
DESCRIPTION	230V IP65 5ft 50W Twin LED Non-Corrosive Emergency - 6000K
NET WEIGHT (KG)	3.25
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Height - 90 Width - 129
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	50
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	5700
LUMENS LIGHT SOURCE ONLY (LM)	6850
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	144.32
LUMENS EMERGENCY MODE (LM)	715
CIRCUIT WATTAGE (W)	47.49
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.216
DISPLACEMENT FACTOR	>0.9
SVM	0.871
PST-LM	0.037
BEAM ANGLE (DEGREES)	120

LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 50W EFFICIENCY FULL LOAD - 90.20% ISOLATION - SELV
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832988687

Date Created: 06/07/2022 14:41

