

Sirius Low Bay 100W 15000 lumens

EL100SFLB3





PRODUCT DATA

LUMENS (Im)	15000lm
DIMMABLE	1-10
WATTAGE (W)	100W
COLOUR TEMPERATURE (K)	5000K
EMERGENCY	YES
WEIGHT (kg)	3.1kg
MICROWAVE	YES
BEAMANGLE	90°
CRI	>80
REPLACEMENT FOR	250W MH/SON
DIMENSIONS (mm)	φ260×175mm
PRODUCT TYPE	Low bays
EFFICIENCY(lm/w)	150lm/W
RATED LIFETIME (hrs)	50,000hrs
IP	65
WORKING ENVIRONMENT	
-30°C to 50°C (5°C to 30°C for Emer.)	
WARRANTY	5
L70 RATING (hrs)	>80000
DAYLIGHT HARVESTING	YES


KEY FEATURES

Ideal for installations at height of 5-8 metres, the Sirius Low Bay 15000 lumen is easy to install with flexible mounting options. It comes with a dimmable driver as standard and Philips Lumiled chips to ensure high efficiency and reliability. Perfect for projects and installations of all sizes.


COMMERCIAL APPLICATIONS

Warehouses, factories, sports arenas, sports halls, retail outlets


POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS





+44 (0)1928 242 918 | sales@novah.co.uk | www.novah.co.uk