

DATA SHEET

ACCESSORIES

M3 Pack V2 LiFePO4 For Recessed Product Ranges

Plug And Play Option For A Range Of Fittings
Comes Complete With Loop in / Loop Out Connectors
Lithium Iron Phosphate Battery LiFePO4



GENERAL INFORMATION	
Product Code	N/REC/M3/PACK/V2
Product Range	Accessories
Product Category	LED Panels
Fixing Method	Recessed
IP Rating	N/A
IK Rating	N/A
Warranty	5 Years 20000 Hours
DIMENSION/WEIGHT	
Dimensions (L x W x D x DIA) (mm)	L=330, W=61, D=30, DIA=N/A
Cut-out Size (mm)	N/A
Product Weight (Kg)	0.41
CONSTRUCTION	
Body Material	PC
Body Colour	White
Optical Material	N/A
Optical Finish	N/A
Termination	4x2x2.5mm sq. Push In Terminal
Driver - Integral or Remote	Remote
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	N/A
Power Consumption (W)	N/A
Efficacy (lm/c.W)	0
Operating Temp. (Min/Max)	0°C - 25 °C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	N/A
Colour Rendering Index (CRI)	N/A
Lumen Depreciation	N/A
SDCM	N/A
ELECTRICAL INPUT	
Voltage (V)	220-240V AC
Operating Frequency	50
In Rush	N/A
Drivers per MCB*	N/A
Class	Class 2
Power Factor	N/A
Cable Entry	Prewired
ELECTRICAL OUTPUT	
Forward Current (mA)	35 to 100
Forward Voltage (Vf)	20 to 55
EMERGENCY DATA	
Mode of Operation	Non-Maintained
Battery Duration	3 hours
Battery Type	LiFePO4
Battery Specification	6.4V 1.5Ah
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	yes
Certificate of Conformity	yes
Accreditations	N/A
BARCODE	
EAN Number	5055943074118

* GUIDE ONLY