

PL LAMP HOLDERS

NPL9-18
PENDANT FOR 2 & 4 PIN
9-18W PL LAMPS

PL pendant with 6-pin socket for 2 and 4 pin 9-18W PL lamps.



NPLP13
PENDANT FOR 4 PIN 13W
PL LAMPS ONLY

PL pendant with 4-pin socket for 13W lamps only.



NPLP18
PENDANT FOR 4 PIN 18W
PL LAMPS ONLY

PL pendant with 4-pin socket for 18W lamps only.



NPLB9-18
BATTEN HOLDER FOR
2 & 4 PIN 9-18W PL LAMPS

PL battenholder with 6-pin socket for 2 and 4 pin 9-18W PL lamps.



LOW VOLTAGE TRANSFORMER

NCG/XFMR/60
TRANSFORMER 12V 60VA DIMMABLE

- 60VA
- Dimmable with leading edge (triac) dimmers
- Auto-reset short-circuit protection
- Thermal cut-out - non resettable



PHOTO-CELLS

NPECK
PHOTO-ELECTRIC CELL KIT



- 230-240V, 50/60Hz
- 5A switching capacity
- 20 lux on, 80 lux off
- IP65

NPECR
PHOTO-ELECTRIC CELL REMOTE



- 230-240V, 50/60Hz
- 5A switching capacity
- 20 lux on, 80 lux off
- IP65 when fitted
- Dimensions: 52 x 20.5 x 20.5. 17mm clearance hole for installation
- Pre-wired with 300mm, 3 cores

NPECH
PHOTO-ELECTRIC CELL HEAD



- 230-240V, 50/60Hz
- 5A switching capacity
- 20 lux on, 80 lux off
- IP65 when fitted
- NEMA male connector base