


### General Information

Dimensions (mm)	68 (W) x 106 (D) x 272 (H)
Materials	Body: Powdercoated Aluminium
Finish	Grey (RAL7024)
Product Weight (Kg)	1
Ingress Protection	IP44
Mounting	Wall
Warranty (Years)	3

### Supply & Power Information

Input Voltage & Frequency (V~ / Hz)	230 50/60
Safety Class	I
Circuit Wattage (W)	7
LED Wattage (W)	7
Inrush Current/Time	<30A (<0.5s)
Power Factor	0.53
Operating Temperature (°C)	-20 to +50
Critical Temperature (°C)	+85
Driver Information	Integrated
Input Terminations	Terminal Block (Screw Terminals)



### Luminaire Output

Colour Temperature (K)	4000
Colour Render Index (CRI)	>80
Typical Luminous Flux (lm)	370
Efficacy (lm/W)	53
Beam Angle (°)	150
Flicker Free	Yes
LED Lifetime (L70) (Hours)	50,000

### Sensor Information

Installation Height (M)	1.5 to 2
Detection Distance (M)	10
Detection Angle (°)	110
Light Level Settings (Lux)	2 to 2000
Time Delay Settings	10 Seconds to 5 Minutes

### Dimming Information

Dimmable	No
----------	----

