DIMMABLE CONTROL GEAR

Technical Specification

Product Code: OVCGMF0001

Description: 240V~ 29-48W 3 in 1 Multi-function Dimmable Constant Current LED Driver



PIN typ.	Irated	Output Voltage	1	2	3	4
29W	600mA	42VDC		ON	ON	ON
34W	700mA	42VDC	ON		ON	ON
36W	750mA	42VDC			ON	ON
39W	800mA	42VDC		ON		ON
41W	850mA	42VDC				ON
43W	900mA	42VDC	ON	ON	ON	
46W	950mA	42VDC			ON	
48W	1000mA	42VDC		ON		
48W	1050mA	40VDC	ON			
48W	1100mA	38VDC				

General Information

Dimensions	103mm (L) x 68mm (W) x 30mm (D)		
Materials	Housing: Polycarbonate		
Finish	White		
Product Weight	0.195Kg		
Dimmable	Yes (DALI, Switch Dim, 1-10V, 10V PWM)		
Ingress Protection	IP20		
Compatible Fittings	All 30W JURA & INCEPTOR SLATE LED Panels		
Warranty	5 Years		
Supply & Power	·		
Input Voltage & Frequency	200-240V~ 50/60Hz		
Electrical Safety	Class II (Double Insulated)		
Rated Power	29W-48W		
DC Voltage Range	3-42V		
16A Circuit Breaker	(B Curve - 25 Units) @ 230V~, (C Curve - 32 Units) @ 230V~		
Constant Current ADJ Range	DIP Switches		
Ambient Temperature (Ta)	-20°C - +45°C		
Critical Temperature	+75°C		
Turn On Delay	<0.5 Seconds @ 230V~		
Input Terminations	Push-fit Terminals		
Dimming Facility			
Control Type	Switch Dim Using Retractive Switch(es)		
Switch Dim Voltage	230V~ input to driver		
Control Arrangement	Short Press: ON / OFF; Press & Hold: DIM		
Control Type	1-10V / 10V PWM Dimming		
1-10V Parameters	Upto 20 drivers with 30 metres maximum overall length		
1-10V Dimming Information	An additional isolation switch will be required to turn the driver On and Off		
Control Type	DALI		
DALI Control Line Voltage	9.5V to 22.5V		
Connectable Driver	Up To 64 Drivers To One DALI Control Line		
Control Line Length (Max.)	100M Max 2 x 0.50mm ² 150M Max 2 x 0.75mm ² 200M Max 2 x 1.00mm ² 300M Max 2 x 1.50mm ²		

Flicker Free

Compatible Fittings

All 30W LED Panels

(IP20) (<u>5</u>)

Yes

OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 300640 **E:** sales@oviaUK.com | **W:** oviaUK.com

Page 1 of 1 Rev.1. Errors & Omissions excluded Specification is subject to change without notice