


Product Code: OVEM7510

Description: 5W Emergency LED Non-Maintained Open Area Downlight



General Information

Dimensions	183mm (L) x 230mm (W) x 32mm (D)
Materials	Downlight: Polycarbonate
Finish	White
Weight	0.7Kg
Cutout	40mm Diameter
Ingress Protection	IP20
Warranty	4 Years

Supply & Power

Input Voltage & Frequency	220-240V ~ 50/60Hz
Electrical Safety	Class II (Double Insulated)
Input Power	5W
Operation Mode	Non-maintained Only
Ambient Temperature (Ta)	0°C - +40°C
Critical Temperature	+70°C

Luminaire Output

Colour Temperature	5500K
LED Lifetime (L70)	30,000 Hours
Beam Angle	120°
Emergency Luminous Flux	250lm

Emergency Information

Emergency Duration	3 hours minimum
Charging Time	24 Hours
Battery Specification	4.8V 3500mAh Ni-Cd Battery - Serial

Replacement Battery

OVEMB4835NCS	4.8V 3500mAh Ni-Cd Battery - Serial
--------------	-------------------------------------

Open Areas

Mounting Height	Axial/Wall	Axial/Axial	Transverse/Axial	Transverse/Transverse	Transverse/Wall
2.0m	2.5	5.5	5.5	5.5	2.5
2.5m	2.5	6	6	6	2.5
3.0m	3	6.5	6.5	6.5	3

Illuminance values based on a maintenance factor of 0.8

