

R3

R3 IP65 Fire Rated Downlight 4000K



Product Data

Part Code (s)	R095601/4K
Applications	Interior
Warranty	5 years
Certification(s)	CE, RoHS

Physical Data

Colour Finish	White (Standard), Black, Chrome, Brushed Chrome, Antique Brass
Dimensions (mm)	Ø85 x H64
Luminaire Fixing	Recessed
Construction Material	Aluminium
Diffuser Type	Polycarbonate (TP(a) Rated)
Unit Weight	0.30Kg



Dimension Diagram

Electrical Data

Wattage	6W
Voltage Range	AC220-240
Power Factor	>0.90
Inrush Current	<60A
Running Current	DC300mA

Technical Data

Lumens (±5%)	591 (at 4000K)
Efficacy	~99Lm/W
Operating Temperature	-20°C to +45°C
Beam Angle	55°
Operating Hours	>50000
IP Rating	IP65
IK Rating	IK08
Dimming Type	Mains Dimmable

Light Source Data

Kelvins	3000K
CRI	>90Ra
Macadam Ellipse	equal or less than 4 sdc _m
L70 B50	70,000 hours
L80 B50	50,000 hours
L90 B50	25,000 hours
LEDs	Samsung



www.ricomaled.com



0161-451-5924



sales@ricomaled.com