

Product Code: CCA050



T **General Information** Plate Dimensions (mm) 86 (W) x 86 (H) x 9.5 (D) Plate Fixing Centres - Horizontal (mm) 60.3 Style **Rounded Profile** Finish Polar White Materials Front Plate & Fuse Drawer: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Anti Microbial Certified Yes Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50 Resistive Load Rating (A) 13 Fuse Fitted Rating & Type 13A (BS 1362) Termination Type Screw Terminal Size (mm) Terminal Torque Value (Nm) 2.5 Ø5 Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4 Switched No Twin Earth Terminals No Product Marking Fused Flex Outlet Available Yes Flex Outlet Location Front of Plate Flex Outlet Dimension (mm) Ø10 Minimum Back Box Depth (mm) 25 Ingress Protection IP20 Operational Temperature (°C) -5 to +40 Warranty (Years) 10 For cleaning / polishing of products, use only a soft, dry, clean cloth. Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of

bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Description: 13A Fused Connection Unit With Optional Flex Outlet

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

