



Product Code: CCA052

Description: 13A Double Pole Switched Fused Connection Unit With Neon & Optional Flex Outlet





General Information

Plate Dimensions (mm) Plate Fixing Centres - Horizontal (mm) Style Finish Materials	86 (W) x 86 (H) x 9.5 (D) 60.3 Rounded Profile Polar White Front Plate, Rocker Switch & Fuse Drawe Urea Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivate	Terminals: Brass	n -lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Ste	
Anti Microbial Certified	Yes		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Rating & Type	13A (BS 1362)		
Termination Type	Screw		
Terminal Size (mm)	Ø5 Terr	ninal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Switched	Yes		
Double Pole Switch	Yes		
Twin Earth Terminals	No		
Neon Indicator	Yes	Indicator Colour	Red
Product Marking	Fused		
Flex Outlet Available	Yes		
Flex Outlet Location		Outlet Dimension (mm)	Ø10
Minimum Back Box Depth (mm)	25		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		
Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.			

All products have been independently tested with 99.9% of enveloped viruses and 92% of nonenveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com



Page 1 of 1 (18/02/22 Errors & Omissions excluded Specification is subject to change without notice